

P/N MS16998-46

Description

length: 1-1/4", thread: 1/4-28, socket head, self-locking, cadmium plated alloy steel, MS16998 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

NAS1351-4-20P

SKU / Model: MS1699846

Minimum Qty (MOQ): 25

NSN: 5305-00-983-6663

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS16998-46 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	1.210 Inches Minimum And 1.250 Inches Maximum
Fastener Length:	1.210 Inches Minimum And 1.250 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.187 Inches Minimum And 0.190 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/MS16998-46 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/socket+head+cap+screws/MS16998-46 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/socket+head+cap+screws/MS16998-46 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/ms16998-46 and selecting the properties of the pro