



Military-Fasteners.com

P/N MS16998-48L

Description

Fastener Length: 1-3/4", Thread: 1/4-28, Head Width: 3/16", Thread Length: 1-1/4", MS16998 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1699848L
Minimum Qty (MOQ):	10
NSN:	5305-01-338-6784
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N MS16998-48L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.250 Inches Nominal
Fastener Length:	1.710 Inches Minimum And 1.750 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.187 Inches Minimum And 0.190 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Fastener And 45.0 Rockwell C Maximum Fastener
Material:	Plastic Polyamide Locking Featuresteel Fastener
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Qq-p-416,type2,class 3 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS16998-48L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.