

Description

Fastener Length: 2-1/4", Thread: 1/4-28, Head Width: 3/16", Thread Length: 1-1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1699850L
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-286-9781
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	156600, Plastic / Rubber Article Viz:

NO IMAGE
AVAILABLE

P/N MS16998-50L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.210 Inches Minimum And 1.500 Inches Maximum
Fastener Length:	2.210 Inches Minimum And 2.250 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.188 Inches Minimum And 0.190 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Fastener And 45.0 Rockwell C Maximum Fastener
Minimum Yield Strength:	155000 Pounds Per Square Inch
Material:	Plastic Polyamide Locking Feature
Material:	Steel Fastener
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Fastener Or Mil-c-81562 Ty 2 Cl 3 Mil Spec Single Treatment Response Fastener
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	6 Type

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS16998-50L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.