

**Description**

Fastener Length: 0-63/64", Thread: 1/4-24, Head Width: 1/4", Thread Length: 0-63/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS1699859L                                |
| Minimum Qty (MOQ):      | 30 EA                                     |
| NSN:                    | 5305-01-189-6506                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS16998-59L Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.886 Inches Minimum And 1.000 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 0.969 Inches Minimum And 1.000 Inches Maximum                       |
| <b>Head Style:</b>                                    | Flat Chamfer  |
| <b>Head Diameter:</b>                                 | 0.457 Inches Minimum And 0.468 Inches Maximum                       |
| <b>Head Height:</b>                                   | 0.306 Inches Minimum And 0.312 Inches Maximum                       |
| <b>Locking Feature:</b>                               | Strip Threads Or Patch Threads                                      |
| <b>Internal Drive Style:</b>                          | Hexagon   |
| <b>Nominal Thread Diameter:</b>                       | 0.312 Inches  |
| <b>Width Across Flats:</b>                            | 0.2500 Inches Minimum And 0.2530 Inches Maximum                     |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                               | 38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| <b>Minimum Yield Strength:</b>                        | 150000 Pounds Per Square Inch                                       |
| <b>Material:</b>                                      | Steel Overall   |
| <b>Surface Treatment:</b>                             | Chromate Overall And Cadmium Overall                                |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,c1 3 Fed Spec Single Treatment Response Overall       |
| <b>Thread Series Designator:</b>                      | Unf   |
| <b>Nondefinitive Spec/std Data:</b>                   | 6 Type  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS16998-59L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.