

**Description**


Fastener Length: 2-1/4", Thread: 3/8-24, Head Width: 5/16", Thread Length: 1-1/4",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS1699879
Minimum Qty (MOQ):	5
NSN:	5305-00-983-7434
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS16998-79 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.210 Inches Minimum And 1.250 Inches Maximum
<b>Fastener Length:</b>	2.210 Inches Minimum And 2.250 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.550 Inches Minimum And 0.562 Inches Maximum
<b>Head Height:</b>	0.368 Inches Minimum And 0.375 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Width Across Flats:</b>	0.312 Inches Minimum And 0.316 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
<b>Minimum Yield Strength:</b>	130000 Pounds Per Square Inch
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS16998-79> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.