

Description

Fastener Length: 2-1/2", Thread: 3/8-24, Head Width: 5/16", Thread Length: 1-1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[NAS1351-6-40P](#)

| | |
|-------------------------|---|
| SKU / Model: | MS1699880 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-00-983-7453 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS16998-80 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.460 Inches Minimum And 1.500 Inches Maximum |
| Fastener Length: | 2.460 Inches Minimum And 2.500 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.550 Inches Minimum And 0.562 Inches Maximum |
| Head Height: | 0.368 Inches Minimum And 0.375 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.375 Inches |
| Width Across Flats: | 0.312 Inches Minimum And 0.316 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 130000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Aqq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS16998-80> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.