

## P/N MS171502

### **Description**

Length: 7/8", slotted

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS171502

Minimum Qty (MOQ): 25

NSN: 5315-00-058-9737

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS171502 Specifications

Overall Length:	0.860 Inches Minimum And 0.890 Inches Maximum
Diameter:	0.094 Inches Nominal
Material Thickness:	0.022 Inches Nominal
Hardness Rating:	43.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall
Shear Strength:	1000 Double Pounds Per Square Inch
Surface Finish:	80.0 Microinches Outside Diameter
Material:	Steel Comp 410 Overall Or Steel Comp 420 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall
Style Designator:	Slotted

## **How to Order**

Order this spring pin from our inventory online by visiting <a href="https://military-fasteners.com/pins/spring+pins/MS171502">https://military-fasteners.com/pins/spring+pins/MS171502</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.