

**Description**


length: 3/4", diameter: 1/8", corrosion resistant steel, MS1715 series pin

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS171530
Minimum Qty (MOQ):	100
NSN:	5315-01-049-1773
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



\* See page 2 for technical characteristics

## P/N MS171530 Specifications

<b>Overall Length:</b>	0.735 Inches Minimum And 0.765 Inches Maximum
<b>Diameter:</b>	0.131 Inches Minimum And 0.135 Inches Maximum
<b>Material Thickness:</b>	0.028 Inches Nominal
<b>Hardness Rating:</b>	83.0 Rockwell Superficial 15-n Minimum Overall And 87.0 Rockwell Superficial 15-n Maximum Overall
<b>Shear Strength:</b>	2100 Double Pounds Per Square Inch
<b>Surface Finish:</b>	80.0 Microinches Outside Diameter
<b>Material:</b>	Steel Comp 410 Overall
<b>Material Document And Classification:</b>	Ams 5506 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Style Designator:</b>	Slotted

## How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS171530> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.