

**Description**

Hole Diameter: 1-1/4",

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS172207
Minimum Qty (MOQ):	5
NSN:	5310-00-566-8869
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



## P/N MS172207 Specifications

<b>Hole Diameter:</b>	1.193 Inches Minimum And 1.213 Inches Maximum
<b>Outside Diameter:</b>	1.438 Inches Minimum And 1.458 Inches Maximum
<b>Internal Prebent Key Length:</b>	0.094 Inches Minimum And 0.125 Inches Maximum
<b>External Prebent Key Width:</b>	0.146 Inches Minimum And 0.166 Inches Maximum
<b>Internal Prebent Key Width:</b>	0.156 Inches Minimum And 0.176 Inches Maximum
<b>Overall Distance Including Keys:</b>	1.829 Inches Minimum And 1.859 Inches Maximum
<b>External Key Quantity:</b>	13
<b>Material Thickness:</b>	0.046 Inches Minimum And 0.054 Inches Maximum
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Ams 6350 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Phosphate Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2481 Assn Std Single Treatment Response Overall
<b>Style Designator:</b>	Key

## How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS172207> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.