

Description

Hole Diameter: 3/4", retaining ring, MS1722 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS172224
Minimum Qty (MOQ):	5
NSN:	5310-00-862-6994
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N MS172224 Specifications

Hole Diameter:	0.801 Inches Minimum And 0.816 Inches Maximum
Outside Diameter:	1.000 Inches Minimum And 1.020 Inches Maximum
Internal Prebent Key Length:	0.062 Inches Minimum And 0.094 Inches Maximum
External Prebent Key Width:	0.146 Inches Minimum And 0.166 Inches Maximum
Internal Prebent Key Width:	0.156 Inches Minimum And 0.176 Inches Maximum
Overall Distance Including Keys:	1.345 Inches Minimum And 1.375 Inches Maximum
External Key Quantity:	11
Material Thickness:	0.036 Inches Minimum And 0.044 Inches Maximum
Material:	Steel Comp 4130 Overall
Material Document And Classification:	Ams 6350 Assn Std Single Material Response Overall
Surface Treatment:	Phosphate Overall
Surface Treatment Document And Classification:	Ams 2481 Assn Std Single Treatment Response Overall
Style Designator:	Key

How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS172224> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.