

Description

Thread Size: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS172237
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-639-3586
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS172237 Specifications

Thread Pitch Diameters:	+0.4487/+0.4513 Inches
Thread Direction:	Right-hand
Drive Point Depth:	0.054 Inches Minimum And 0.064 Inches Maximum
Nut Style:	Round
Nut Diameter:	0.797 Inches Minimum And 0.817 Inches Maximum
Nut Thickness:	0.188 Inches Nominal
Drive Point Width:	0.125 Inches Nominal
Drive Point Quantity:	8
Thread Series:	Uns
Thread Quantity Per Inch:	32
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Nominal Thread Size:	0.469 Inches
Countersink Angle:	88.0 Degrees Minimum Second End And 92.0 Degrees Maximum Second End
Countersink Angle:	88.0 Degrees Minimum First End And 92.0 Degrees Maximum First End
Material:	Steel Comp 4140 Overall
Material Document And Classification:	Ams 6381 Assn Std Single Material Response Overall Or Ams 6382 Assn Std Single Material Response Overall
Surface Treatment Document And Classification:	Ams 2481 Assn Std Single Treatment Response Overall

How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/spring+pins/MS172237> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.