

Description

Thread Size: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS172242
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-208-3446
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS172242 Specifications

Thread Pitch Diameters:	+1.1369/+1.1409 Inches
Thread Direction:	Right-hand
Drive Point Depth:	0.086 Inches Minimum And 0.096 Inches Maximum
Nut Style:	Round
Nut Diameter:	1.673 Inches Minimum And 1.693 Inches Maximum
Nut Thickness:	0.271 Inches Minimum And 0.291 Inches Maximum
Drive Point Width:	0.178 Inches Minimum And 0.198 Inches Maximum
Drive Point Quantity:	8
Thread Series:	Uns
Features Provided:	Casehardened
Thread Quantity Per Inch:	18
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Nominal Thread Size:	1.173 Inches
Countersink Angle:	90.0 Degrees Nominal Nut
Material:	Steel Comp 4140 Overall
Material Document And Classification:	Ams 6381 Assn Std Single Material Response Overall Or Ams 6382 Assn Std Single Material Response Overall

How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/spring+pins/MS172242> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.