

**Description**

Thread Size: 1-1/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS172242
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-208-3446
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS172242 Specifications

<b>Thread Pitch Diameters:</b>	+1.1369/+1.1409 Inches
<b>Thread Direction:</b>	Right-hand
<b>Drive Point Depth:</b>	0.086 Inches Minimum And 0.096 Inches Maximum
<b>Nut Style:</b>	Round
<b>Nut Diameter:</b>	1.673 Inches Minimum And 1.693 Inches Maximum
<b>Nut Thickness:</b>	0.271 Inches Minimum And 0.291 Inches Maximum
<b>Drive Point Width:</b>	0.178 Inches Minimum And 0.198 Inches Maximum
<b>Drive Point Quantity:</b>	8
<b>Thread Series:</b>	Uns
<b>Features Provided:</b>	Casehardened
<b>Thread Quantity Per Inch:</b>	18
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
<b>Nominal Thread Size:</b>	1.173 Inches
<b>Countersink Angle:</b>	90.0 Degrees Nominal Nut
<b>Material:</b>	Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	Ams 6381 Assn Std Single Material Response Overall Or Ams 6382 Assn Std Single Material Response Overall

## How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/spring+pins/MS172242> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.