

**Description**

Thread Size: 1-3/4

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS172245
Minimum Qty (MOQ):	2
NSN:	5310-00-817-2402
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS172245 Specifications

<b>Thread Pitch Diameters:</b>	+1.7309/+1.7354 Inches
<b>Thread Direction:</b>	Right-hand
<b>Drive Point Depth:</b>	0.086 Inches Minimum And 0.096 Inches Maximum
<b>Nut Style:</b>	Round
<b>Nut Diameter:</b>	2.297 Inches Minimum And 2.317 Inches Maximum
<b>Nut Thickness:</b>	0.312 Inches Nominal
<b>Drive Point Width:</b>	0.250 Inches Nominal
<b>Drive Point Quantity:</b>	8
<b>Thread Series:</b>	Uns
<b>Thread Quantity Per Inch:</b>	18
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
<b>Nominal Thread Size:</b>	1.766 Inches
<b>Countersink Angle:</b>	88.0 Degrees Minimum Second End And 92.0 Degrees Maximum Second End
<b>Countersink Angle:</b>	88.0 Degrees Minimum First End And 92.0 Degrees Maximum First End
<b>Material:</b>	Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	Ams 6381 Assn Std Single Material Response Overall Or Ams6382 Assn Std Single Material Response Overall

## How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/spring+pins/MS172245> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.