

P/N MS172325

Military-Fasteners.com

Description

Thread Size: 3/4"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS172325
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-533-9186
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS172325 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Drive Point Depth:	0.055 Inches Minimum And 0.065 Inches Maximum
Nut Style:	Round
Nut Diameter:	1.376 Inches Minimum And 1.396 Inches Maximum
Nut Thickness:	0.250 Inches Nominal
Drive Point Width:	0.178 Inches Minimum And 0.198 Inches Maximum
Drive Point Quantity:	8
Thread Series:	Unef
Thread Quantity Per Inch:	20
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Nominal Thread Size:	0.750 Inches
Countersink Angle:	90.0 Degrees Nominal Nut
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Ams 6381 Assn Std 1st Material Response Overall Or Ams 6382 Assn Std 1st Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Phosphate Overall
Surface Treatment Document And Classification:	Ams 2481 Assn Std Single Treatment Response Overall

How to Order

Order this nut from our inventory online by visiting <u>https://military-fasteners.com/nuts/spring+pins/MS172325</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.