

Description

Thread Size: 7/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS172327
Minimum Qty (MOQ):	5
NSN:	5310-00-834-8815
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N MS172327 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Drive Point Depth:	0.062 Inches Nominal
Nut Style:	Round
Nut Diameter:	1.516 Inches Minimum And 1.536 Inches Maximum
Nut Thickness:	0.240 Inches Minimum And 0.260 Inches Maximum
Drive Point Width:	0.178 Inches Minimum And 0.198 Inches Maximum
Drive Point Quantity:	8
Thread Series:	Unef
Features Provided:	Casehardened
Thread Quantity Per Inch:	20
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Nominal Thread Size:	0.875 Inches
Material:	Steel Comp 4140 Overall
Material Document And Classification:	Ams 6381 Assn Std Single Material Response Overall Or Ams 6382 Assn Std Single Material Response Overall
Surface Treatment:	Phosphate Overall
Surface Treatment Document And Classification:	Ams 2481 Assn Std Single Treatment Response Overall

How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/spring+pins/MS172327> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.