

Description

Thread Size: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | MS172333 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5310-00-985-0216 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS172333 Specifications

| | |
|----------------------------------------------|----------------------------------------------------------------------------------------------------------|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Drive Point Depth: | 0.094 Inches Nominal |
| Nut Style: | Round |
| Nut Diameter: | 1.985 Inches Minimum And 2.005 Inches Maximum |
| Nut Thickness: | 0.281 Inches Nominal |
| Drive Point Width: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Drive Point Quantity: | 8 |
| Thread Series: | Unef |
| Thread Quantity Per Inch: | 18 |
| Nominal Thread Size: | 1.250 Inches |
| Countersink Angle: | 88.0 Degrees Minimum Nut And 92.0 Degrees Maximum Nut |
| Material: | Steel Comp 4140 Overall |
| Material Document And Classification: | Ams 6381 Assn Std Single Material Response Overall Or Ams 6382 Assn Std Single Material Response Overall |
| Surface Treatment: | Phosphate Overall |

How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/spring+pins/MS172333> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.