

**Description**

Thread Size: 1-3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS172340
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-837-9908
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS172340 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Drive Point Depth:</b>	0.094 Inches Nominal
<b>Nut Style:</b>	Round
<b>Nut Diameter:</b>	2.423 Inches Minimum And 2.443 Inches Maximum
<b>Nut Thickness:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Drive Point Width:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Drive Point Quantity:</b>	8
<b>Thread Series:</b>	Unef
<b>Features Provided:</b>	Casehardened
<b>Thread Quantity Per Inch:</b>	18
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
<b>Nominal Thread Size:</b>	1.688 Inches
<b>Material:</b>	Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	Ams 6381 Assn Std Single Material Response Overall Or Ams 6382 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Phosphate Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2481 Assn Std Single Treatment Response Overall

## How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/spring+pins/MS172340> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.