

Description

Thread Size: 2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS172345 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5310-00-050-0240 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS172345 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Drive Point Depth: | 0.093 Inches Nominal |
| Nut Style: | Round |
| Nut Diameter: | 2.766 Inches Minimum And 2.786 Inches Maximum |
| Nut Thickness: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Drive Point Width: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Drive Point Quantity: | 8 |
| Thread Series: | Un |
| Thread Quantity Per Inch: | 16 |
| Hardness Rating: | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum |
| Nominal Thread Size: | 2.000 Inches |
| Countersink Angle: | 90.0 Degrees Nominal Nut |
| Material: | Steel Comp 4140 Overall |
| Material Document And Classification: | Ams 6382 Assn Std Single Material Response Overall Or Ams 6381 Assn Std Single Material Response Overall |
| Surface Treatment: | Phosphate Overall |
| Surface Treatment Document And Classification: | Ams 2481 Assn Std Single Treatment Response Overall |

How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/spring+pins/MS172345> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.