

Description

Thread Size: 2-1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS172349
Minimum Qty (MOQ):	1 EA
NSN:	5310-00-935-3658
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS172349 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Drive Point Depth:	0.086 Inches Minimum And 0.096 Inches Maximum
Nut Style:	Round
Nut Diameter:	3.016 Inches Minimum And 3.036 Inches Maximum
Nut Thickness:	0.312 Inches Nominal
Drive Point Width:	0.240 Inches Minimum And 0.260 Inches Maximum
Drive Point Quantity:	8
Thread Series:	Un
Thread Quantity Per Inch:	16
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Nominal Thread Size:	2.250 Inches
Countersink Angle:	88.0 Degrees Minimum Second End And 92.0 Degrees Maximum Second End
Countersink Angle:	88.0 Degrees Minimum First End And 92.0 Degrees Maximum First End
Material:	Steel Comp 4140 Overall
Material Document And Classification:	Ams 6381 Assn Std Single Material Response Overall Or Ams6382 Assn Std Single Material Response Overall
Surface Treatment:	Phosphate Overall
Surface Treatment Document And Classification:	Ams 2481 Assn Std Single Treatment Response Overall

How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/spring+pins/MS172349> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.