

P/N MS172349

Description

Thread Size: 2-1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS172349

Minimum Qty (MOQ): 1 EA

NSN: 5310-00-935-3658

Schedule B: 7318.16.0085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS172349 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Drive Point Depth:	0.086 Inches Minimum And 0.096 Inches Maximum
Nut Style:	Round
Nut Diameter:	3.016 Inches Minimum And 3.036 Inches Maximum
Nut Thickness:	0.312 Inches Nominal
Drive Point Width:	0.240 Inches Minimum And 0.260 Inches Maximum
Drive Point Quantity:	8
Thread Series:	Un
Thread Quantity Per Inch:	16
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Nominal Thread Size:	2.250 Inches
Countersink Angle:	88.0 Degrees Minimum Second End And 92.0 Degrees Maximum Second End
Countersink Angle:	88.0 Degrees Minimum First End And 92.0 Degrees Maximum First End
Material:	Steel Comp 4140 Overall
Material Document And Classification:	Ams 6381 Assn Std Single Material Response Overall Or Ams6382 Assn Std Single Material Response Overall
Surface Treatment:	Phosphate Overall
Surface Treatment Document And Classification:	Ams 2481 Assn Std Single Treatment Response Overall

How to Order

Order this nut from our inventory online by visiting https://military-fasteners.com/nuts/spring+pins/MS172349 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/spring+pins/MS172349 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/spring+pins/MS172349 and selecting the quantity you want then click "add to cart".