

P/N MS17829-4C

Description

MS17829-4C Self-Locking Hexagon Nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS178294C

Minimum Qty (MOQ): 10

NSN: 5310-00-483-8792

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS17829-4C Specifications

| Thread Class: | 3b |
|--|---|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Nut Style: | Hexagon |
| Nut Height: | 0.240 Inches Minimum And 0.360 Inches Maximum |
| End Item Identification: | Mrap Buffalo Mk2a2 |
| Width Across Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Temp Rating: | 250.0 Deg Fahrenheit Nominal |
| Thread Series: | Unc |
| Thread Quantity Per Inch: | 20 |
| Nominal Thread Size: | 0.250 Inches |
| Countersink Angle: | 88.0 Degrees Nominal Nut |
| Bearing Surface Type: | Chamfered Or Washer Faced |
| Material: | Plastic Polyhexamethylene Amide Locking Insert |
| Material: | Steel Comp 1137 Nut |
| Material Document And Classification: | 66 Fed Std Single Material Response Locking Insert |
| Surface Treatment: | Cadmium Nut |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Nut |

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS17829-4C and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS17829-4C and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS17829-4C and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS17829-4C and selecting the properties of the