

P/N MS17830-12C

Description

Thread: 3/4-10, Nut Height: 7/8", MS17830 series nut

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS1783012C

Minimum Qty (MOQ): 2

NSN: 5310-00-241-6609

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N MS17830-12C Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Nut Style:	Hexagon
Nut Height:	0.855 Inches Minimum And 0.891 Inches Maximum
Width Across Flats:	1.052 Inches Minimum And 1.064 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unc
Thread Quantity Per Inch:	10
Nominal Thread Size:	0.750 Inches
Countersink Angle:	88.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered
Bearing Surface Finish:	125.0 Microinches
Material:	Plastic Polyhexamethylene Amide Locking Insert
Material:	Steel Comp 301 Nut Or Steel Comp 302 Nut Or Steel Comp 303 Nut Or Steel Comp 303f Nut Or Steel Comp 303s Nut Or Steel Comp 304 Nut Or Steel Comp 304 Nut Or Steel Comp 305 Nut Or Steel Comp 308 Nut Or Steel Comp 309 Nut Or Steel Comp 310 Nut Or Steel Comp 310s Nut Or Steel Comp 314 Nut Or Steel Comp 316 Nut Or Steel Comp 316 Nut Or Steel Comp 317 Nut Or Steel Comp 321 Nut Or Steel Comp 323 Nut Or Steel Comp 324 Nut Or Steel Comp 348 Nut Or Steel Comp 385 Nut Or Steel Comp 302b Nut Or Steel Comp 384 Nut
Material Document And Classification:	66 Fed Std All Material Responses Nut
Material Document And Classification:	Mil-m-20693,comp A,ty 1 Mil Spec Single Material Response Locking Insert
Surface Treatment:	Passivate Nut
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Nut

How to Order

