

P/N MS17830-8C

Description

Thread Size: 1/2", Nut Height: 5/8", Head Width: 3/4", MS17830 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS178308C

Minimum Qty (MOQ):

NSN: 5310-00-411-4385

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS17830-8C Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Nut Style:	Hexagon
Nut Height:	0.575 Inches Minimum And 0.610 Inches Maximum
Width Across Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unc
Thread Quantity Per Inch:	13
Nominal Thread Size:	0.500 Inches
Countersink Angle:	88.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered
Bearing Surface Finish:	125.0 Microinches
Material:	Plastic Polyhexamethylene Amide Locking Insert
Material:	Steel Comp 301 Nut Or Steel Comp 302 Nut Or Steel Comp 302b Nut Or Steel Comp 303 Nut Or Steel Comp 303se Nut Or Steel Comp 304 Nut Or Steel Comp 304 Nut Or Steel Comp 305 Nut Or Steel Comp 305 Nut Or Steel Comp 305 Nut Or Steel Comp 310 Nut Or Steel Comp 316 Nut Or Steel Comp 316 Nut Or Steel Comp 317 Nut Or Steel Comp 321 Nut Or Steel Comp 347 Nut Or Steel Comp 348 Nut Or Steel Comp 385 Nut
Material Document And Classification:	66 Fed Std All Material Responses Nut
Material Document And Classification:	Mil-m-20693,comp A,ty 1 Mil Spec Single Material Response Locking Insert
Surface Treatment:	Passivate Nut
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Nut

How to Order

