

**Description**

MS17984C403 Quick Release Pin

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS17984-C403](#)

SKU / Model:	MS17984C403
Minimum Qty (MOQ):	1
NSN:	5315-00-962-4476
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



## P/N MS17984C403 Specifications

<b>Shank Diameter:</b>	0.2470 Inches Minimum And 0.2485 Inches Maximum
<b>Button Handle Diameter:</b>	0.720 Inches Minimum And 0.800 Inches Maximum
<b>Detent Quantity:</b>	2
<b>Actuation Method:</b>	Push Button
<b>Grip Length:</b>	0.300 Inches Minimum And 0.320 Inches Maximum
<b>Actuation Type:</b>	Push
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum Shank
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum Spindle
<b>Shoulder To Head End Distance:</b>	0.890 Inches Maximum
<b>Pin Attachment Type:</b>	Hook Or Ring
<b>Detent To Tapered End Distance:</b>	0.260 Inches Minimum And 0.290 Inches Maximum
<b>Material:</b>	Steel Comp 630 Shank Or Steel Comp 632 Shank
<b>Material:</b>	Steel Comp 630 Spindle Or Steel Comp 632 Spindle
<b>Material Document And Classification:</b>	Ams 5643 Assn Std 1st Material Response Shank Or Ams 5657 Assn Std 2nd Material Response Shank
<b>Material Document And Classification:</b>	Ams 5643 Assn Std 1st Material Response Spindle Or Ams 5657 Assn Std 2nd Material Response Spindle
<b>Surface Treatment:</b>	Passivate Shank
<b>Surface Treatment:</b>	Passivate Spindle
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Shank
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Spindle
<b>Style Designator:</b>	Button

## How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/MS17984C403> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.