

Description

MS17984C420 Quick Release Pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS17984C420
Minimum Qty (MOQ):	2
NSN:	5315-00-904-1671
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS17984C420 Specifications

Shank Diameter:	0.2470 Inches Minimum And 0.2485 Inches Maximum
Button Handle Diameter:	0.720 Inches Minimum And 0.800 Inches Maximum
Detent Quantity:	2
Actuation Method:	Push Button
Grip Length:	2.000 Inches Minimum And 2.020 Inches Maximum
Actuation Type:	Push
Hardness Rating:	40.0 Rockwell C Minimum Shank
Hardness Rating:	40.0 Rockwell C Minimum Spindle
Shoulder To Head End Distance:	0.890 Inches Maximum
Pin Attachment Type:	Hook Or Ring
Detent To Tapered End Distance:	0.260 Inches Minimum And 0.290 Inches Maximum
Material:	Steel Comp 630 Shank Or Steel Comp 632 Shank
Material:	Steel Comp 630 Spindle Or Steel Comp 632 Spindle
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Shank Or Ams 5657 Assn Std 2nd Material Response Shank
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Spindle Or Ams 5657 Assn Std 2nd Material Response Spindle
Surface Treatment:	Passivate Shank
Surface Treatment:	Passivate Spindle
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Shank
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Spindle
Style Designator:	Button

How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/MS17984C420> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.