

**Description**

MS17984C508 Quick Release Pin

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS17984C508
Minimum Qty (MOQ):	2
NSN:	5315-00-904-6182
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

# P/N MS17984C508 Specifications

<b>Shank Diameter:</b>	0.3095 Inches Minimum And 0.3110 Inches Maximum
<b>Button Handle Diameter:</b>	0.810 Inches Minimum And 1.135 Inches Maximum
<b>Detent Quantity:</b>	2
<b>Actuation Method:</b>	Push Button
<b>End Item Identification:</b>	W/s: Engine, Aircraft F110-ge-400; M1a2 Abrams Tank, 2350-01-328-5964 (eaa Cmbt85sep); M1a2 Heavy Assault Bridge (hab)/wolverine, 5420-01-430-4247; M1a2 System Enhancement Prog 2350-01-328-5964 (eaa Cmbt85sep); Missile, Minuteman Lgm-30; Aircraft, Stratolifter C-135; Tank, Abrams M-1; Troposcatter Radio Terminal System Antrc170; Tank, Combat, Ft, 120mm Gun (m1a1); Support Equipment, Mx Peacekeeper Missile
<b>Grip Length:</b>	0.800 Inches Minimum And 0.820 Inches Maximum
<b>Actuation Type:</b>	Push
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum Shank
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum Spindle
<b>Shear Strength:</b>	14400 Double Pound
<b>Shoulder To Head End Distance:</b>	0.930 Inches Maximum
<b>Pin Attachment Type:</b>	Hook Or Ring
<b>Detent To Tapered End Distance:</b>	0.300 Inches Minimum And 0.330 Inches Maximum
<b>Material:</b>	Steel Comp 630 Shank Or Steel Comp 632 Shank
<b>Material:</b>	Steel Comp 630 Spindle Or Steel Comp 632 Spindle
<b>Material Document And Classification:</b>	Ams 5643 Assn Std 1st Material Response Shank Or Ams 5657 Assn Std 2nd Material Response Shank
<b>Material Document And Classification:</b>	Ams 5643 Assn Std 1st Material Response Spindle Or Ams 5657 Assn Std 2nd Material Response Spindle
<b>Surface Treatment:</b>	Passivate Shank
<b>Surface Treatment:</b>	Passivate Spindle
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Shank
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Spindle
<b>Style Designator:</b>	Button

## How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/MS17984C508> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.