

**Description**

MS17984 series pin

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                             |
|-------------------------|-----------------------------|
| SKU / Model:            | MS17984C615                 |
| Minimum Qty (MOQ):      | 1                           |
| NSN:                    | 5315-00-937-0965            |
| Schedule B:             | 7318.24.0000                |
| ECCN:                   | EAR99                       |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



\* See page 2 for technical characteristics

## P/N MS17984C615 Specifications

|   |   |
|---|---|
| <b>Shank Diameter:</b>                                | 0.3720 Inches Minimum And 0.3735 Inches Maximum   |
| <b>Button Handle Diameter:</b>                        | 0.875 Inches Minimum And 1.135 Inches Maximum   |
| <b>Detent Quantity:</b>                               | 2   |
| <b>End Item Identification:</b>                       | W/s:ah-64-d Longbow; Missile, All-weather Antiship, Harpoon (agm-84); Helicopter, Mh-53e; Engine, Aircraft, F100-pw-200 (f-16a/b/c/d); Lav, Anti-tank; Missile, Minuteman Lgm-30; Boat, Bridge Erection, Uscsbmk2; Field Artillery Ammunition Support Vehicle (faagv)(m992); Navstar Global Positioning System User Equipment (ue); Engine, Aircraft F100-pw-229 (f15e, F16c/d) |
| <b>Grip Length:</b>                                   | 1.500 Inches Minimum And 1.520 Inches Maximum   |
| <b>Actuation Type:</b>                                | Push  |
| <b>Hardness Rating:</b>                               | 40.0 Rockwell C Minimum Overall   |
| <b>Shoulder To Head End Distance:</b>                 | 1.040 Inches Maximum  |
| <b>Pin Attachment Type:</b>                           | Hook  |
| <b>Detent To Tapered End Distance:</b>                | 0.335 Inches Minimum And 0.365 Inches Maximum   |
| <b>Material:</b>                                      | Steel Comp 630 Shank Or Steel Comp 632 Shank  |
| <b>Material:</b>                                      | Steel Comp 630 Spindle Or Steel Comp 632 Spindle  |
| <b>Material Document And Classification:</b>          | Ams 5643 Assn Std 1st Material Response Shank Or Ams 5657 Assn Std 2nd Material Response Shank  |
| <b>Material Document And Classification:</b>          | Ams 5643 Assn Std 1st Material Response Spindle Or Ams 5657 Assn Std 2nd Material Response Spindle  |
| <b>Surface Treatment:</b>                             | Passivate Shank   |
| <b>Surface Treatment:</b>                             | Passivate Spindle   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Shank  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Spindle  |
| <b>Style Designator:</b>                              | Button  |

## How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/MS17984C615> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.