

P/N MS17986C310

Military-Fasteners.com

### Description

MS17986C310 Quick Release Pin

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

# Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

#### MS17986-C310

SKU / Model:	MS17986C310
Minimum Qty (MOQ):	1
NSN:	5315-00-959-6648
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



# P/N MS17986C310 Specifications

Shank Diameter:	0.187 Inches Minimum And 0.188 Inches Maximum
Detent Quantity:	2
Actuation Method:	Push Button
Grip Length:	1.000 Inches Minimum And 1.020 Inches Maximum
Actuation Type:	Push
Hardness Rating:	40.0 Rockwell C Minimum Overall
Shoulder To Head End Distance:	1.270 Inches Nominal
Pin Center To Handle End Distance:	1.460 Inches Nominal
Pin Attachment Type:	Hook Or Ring
Detent To Tapered End Distance:	0.260 Inches Nominal
Material:	Steel Comp 630 Overall Or Steel Comp 632 Overall
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Overall Or Ams 5657 Assn Std 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	L Handle

## **How to Order**

Order this quick release pin from our inventory online by visiting <u>https://military-fasteners.com/pins/quick+release+pins/MS17986C310</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.