

Description

Quick Release Pin part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS17986C419
Minimum Qty (MOQ):	1
NSN:	5315-01-236-1988
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS17986C419 Specifications

Shank Diameter:	0.2470 Inches Minimum And 0.2485 Inches Maximum
Detent Quantity:	2
Actuation Method:	Push Button
Grip Length:	1.900 Inches Minimum And 1.920 Inches Maximum
Actuation Type:	Push
Hardness Rating:	40.0 Rockwell C Minimum Shank
Hardness Rating:	40.0 Rockwell C Minimum Spindle
Shear Strength:	9200 Double Pounds Per Square Inch
Shoulder To Head End Distance:	1.270 Inches Maximum
Pin Center To Handle End Distance:	1.420 Inches Nominal
Detent To Tapered End Distance:	0.260 Inches Minimum And 0.290 Inches Maximum
Special Features:	Includes And Attachingring Or Link
Material:	Steel Comp 630 Shank
Material:	Steel Comp 630 Spindle
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Shank
Material Document And Classification:	Ams 5643 Assn Std 2nd Material Response Spindle
Surface Treatment:	Passivate Shank
Surface Treatment:	Passivate Spindle
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 1st Treatment Response Shank
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 2nd Treatment Response Spindle
Style Designator:	L Handle

How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/MS17986C419> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.