

**Description**

Quick Release Pin part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS17986C419
Minimum Qty (MOQ):	1
NSN:	5315-01-236-1988
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

## P/N MS17986C419 Specifications

<b>Shank Diameter:</b>	0.2470 Inches Minimum And 0.2485 Inches Maximum
<b>Detent Quantity:</b>	2
<b>Actuation Method:</b>	Push Button
<b>Grip Length:</b>	1.900 Inches Minimum And 1.920 Inches Maximum
<b>Actuation Type:</b>	Push
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum Shank
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum Spindle
<b>Shear Strength:</b>	9200 Double Pounds Per Square Inch
<b>Shoulder To Head End Distance:</b>	1.270 Inches Maximum
<b>Pin Center To Handle End Distance:</b>	1.420 Inches Nominal
<b>Detent To Tapered End Distance:</b>	0.260 Inches Minimum And 0.290 Inches Maximum
<b>Special Features:</b>	Includes And Attachingring Or Link
<b>Material:</b>	Steel Comp 630 Shank
<b>Material:</b>	Steel Comp 630 Spindle
<b>Material Document And Classification:</b>	Ams 5643 Assn Std 1st Material Response Shank
<b>Material Document And Classification:</b>	Ams 5643 Assn Std 2nd Material Response Spindle
<b>Surface Treatment:</b>	Passivate Shank
<b>Surface Treatment:</b>	Passivate Spindle
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec 1st Treatment Response Shank
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec 2nd Treatment Response Spindle
<b>Style Designator:</b>	L Handle

## How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/MS17986C419> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.