

Description

Quick Release Pin part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS17986C521
Minimum Qty (MOQ):	1
NSN:	5315-00-855-7801
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS17986C521 Specifications

Shank Diameter:	0.3095 Inches Minimum And 0.3120 Inches Maximum
Actuation Method:	Push Button
Grip Length:	2.100 Nominal Mils And 2.120 Nominal Centimeters
Actuation Type:	Push
Hardness Rating:	40.0 Rockwell C Minimum Shank
Hardness Rating:	54.0 Rockwell C Minimum Detent And 64.0 Rockwell C Maximum Detent
Shoulder To Head End Distance:	1.550 Inches Nominal
Pin Center To Handle End Distance:	1.780 Inches Nominal
Pin Attachment Type:	Ring
Detent To Tapered End Distance:	0.400 Inches Nominal
Material:	Steel Comp 630 Shank Or Steel Comp 632 Shank
Material:	Steel Comp 630 Spindle Or Steel Comp 632 Spindle
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Shank Or Ams 5657 Assn Std 2nd Material Response Shank
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Spindle Or Ams 5657 Assn Std 2nd Material Response Spindle
Surface Treatment:	Passivate Shank
Surface Treatment:	Passivate Spindle
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Shank
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Spindle
Style Designator:	L Handle
Specification/standard Data:	80205-nas1335 Professional/Industrial Association Standard

How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/MS17986C521> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.