

P/N MS17986C610

Description

Grip Length: 1", MS17986 series pin

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS17986C610
Minimum Qty (MOQ):	1
NSN:	5315-00-904-6859
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



^{*} See page 2 for technical characteristics

P/N MS17986C610 Specifications

Shank Diameter: 0.3720 Inches Minimum And 0.3735 Inches Maximum Detent Quantity: 2 Actuation Method: Push Button	
Actuation Method: Push Button	
1 4311 5414411	
Grip Length: 1.000 Inches Minimum And 1.020 Inches Maximum	
Actuation Type: Push	
Hardness Rating: 40.0 Rockwell C Minimum Shank	
Hardness Rating: 40.0 Rockwell C Minimum Spindle	
Shoulder To Head End Distance: 1.450 Inches Maximum	
Pin Center To Handle End Distance: 1.640 Inches Maximum	
Pin Attachment Type: Hook Or Ring	
Detent To Tapered End Distance: 0.335 Inches Minimum And 0.365 Inches Maximum	
Material: Steel Comp 630 Shank Or Steel Comp 632 Shank	
Material: Steel Comp 630 Spindle Or Steel Comp 632 Spindle	
Material Document And Classification: Ams 5643 Assn Std 1st Material Response Shank Or Ams 5657 Assn Std 2nd Material Response Shank Or	hank
Material Document And Classification: Ams 5643 Assn Std 1st Material Response Spindle Or Ams 5657 Assn Std 2nd Material Response Spindle Or Ams 5657 Assn Std 2	Spindle
Surface Treatment: Passivate Shank	
Surface Treatment: Passivate Spindle	
Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Shank	
Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Spindle	
Style Designator: L Handle	

How to Order

Order this quick release pin from our inventory online by visiting https://military-fasteners.com/pins/quick+release+pins/MS17986C610 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.