

Description

Pin part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS17986C616 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5315-00-975-2481 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

P/N MS17986C616 Specifications

| | |
|---|--|
| Shank Diameter: | 0.3720 Inches Minimum And 0.3735 Inches Maximum |
| Detent Quantity: | 2 |
| Actuation Method: | Push Button |
| Grip Length: | 1.600 Inches Minimum And 1.620 Inches Maximum |
| Actuation Type: | Push |
| Hardness Rating: | 40.0 Rockwell C Minimum Shank |
| Hardness Rating: | 40.0 Rockwell C Minimum Spindle |
| Shoulder To Head End Distance: | 1.450 Inches Maximum |
| Pin Center To Handle End Distance: | 1.640 Inches Maximum |
| Pin Attachment Type: | Hook Or Ring |
| Detent To Tapered End Distance: | 0.335 Inches Minimum And 0.365 Inches Maximum |
| Material: | Steel Comp 630 Shank Or Steel Comp 632 Shank |
| Material: | Steel Comp 630 Spindle Or Steel Comp 632 Spindle |
| Material Document And Classification: | Ams 5643 Assn Std 1st Material Response Shank Or Ams 5657 Assn Std 2nd Material Response Shank |
| Material Document And Classification: | Ams 5643 Assn Std 1st Material Response Spindle Or Ams 5657 Assn Std 2nd Material Response Spindle |
| Surface Treatment: | Passivate Shank |
| Surface Treatment: | Passivate Spindle |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Shank |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Spindle |
| Style Designator: | L Handle |

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS17986C616> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.