

Description

Pin part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS17986C620
Minimum Qty (MOQ):	1 EA
NSN:	5315-00-470-3224
National Motor Freight:	013120, Aluminum Article Noi Sub 6

NO IMAGE
AVAILABLE

P/N MS17986C620 Specifications

Shank Diameter:	0.3720 Inches Minimum And 0.3735 Inches Maximum
Detent Quantity:	2
Actuation Method:	Push Button
Grip Length:	2.000 Inches Minimum And 2.020 Inches Maximum
Actuation Type:	Push
Hardness Rating:	40.0 Rockwell C Minimum Shank
Hardness Rating:	40.0 Rockwell C Minimum Spindle
Shoulder To Head End Distance:	1.450 Inches Maximum
Pin Center To Handle End Distance:	1.555 Inches Minimum And 1.640 Inches Maximum
Pin Attachment Type:	Hook Or Ring
Detent To Tapered End Distance:	0.335 Inches Minimum And 0.365 Inches Maximum
Material:	Steel Comp 630 Shank Or Steel Comp 632 Shank
Material:	Steel Comp 630 Spindle Or Steel Comp 632 Spindle
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Shank Or Ams 5657 Assn Std 2nd Material Response Shank
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Spindle Or Ams 5657 Assn Std 2nd Material Response Spindle
Surface Treatment:	Passivate Shank
Surface Treatment:	Passivate Spindle
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Shank
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Spindle
Style Designator:	L Handle

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS17986C620> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.