

**Description**

Pin part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS17986C809
Minimum Qty (MOQ):	1 EA
NSN:	5315-01-211-7547
National Motor Freight:	105840, Nails / Spikes I / S Noi Plain Etc



NO IMAGE  
AVAILABLE

## P/N MS17986C809 Specifications

<b>Shank Diameter:</b>	0.4970 Inches Minimum And 0.4985 Inches Maximum
<b>Detent Quantity:</b>	2
<b>Actuation Method:</b>	Push Button
<b>Grip Length:</b>	0.900 Inches Minimum And 0.920 Inches Maximum
<b>Actuation Type:</b>	Push
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum Shank
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum Spindle
<b>Shoulder To Head End Distance:</b>	1.600 Inches Maximum
<b>Pin Center To Handle End Distance:</b>	1.730 Inches Minimum
<b>Pin Attachment Type:</b>	Link Or Ring
<b>Detent To Tapered End Distance:</b>	0.430 Inches Minimum And 0.460 Inches Maximum
<b>Material:</b>	Steel Comp 630 Shank Or Steel Comp 632 Shank
<b>Material:</b>	Steel Comp 630 Spindle Or Steel Comp 632 Spindle
<b>Material Document And Classification:</b>	Ams 5643 Assn Std 1st Material Response Shank Or Ams 5657 Assn Std 2nd Material Response Shank
<b>Material Document And Classification:</b>	Ams 5643 Assn Std 1st Material Response Spindle Or Ams 5657 Assn Std 2nd Material Response Spindle
<b>Surface Treatment:</b>	Passivate Shank
<b>Surface Treatment:</b>	Passivate Spindle
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Shank
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Spindle
<b>Style Designator:</b>	L Handle

## How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS17986C809> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.