

Description

Pin part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS17986C809
Minimum Qty (MOQ):	1 EA
NSN:	5315-01-211-7547
National Motor Freight:	105840, Nails / Spikes I / S Noi Plain Etc



* See page 2 for technical characteristics

P/N MS17986C809 Specifications

Shank Diameter:	0.4970 Inches Minimum And 0.4985 Inches Maximum
Detent Quantity:	2
Actuation Method:	Push Button
Grip Length:	0.900 Inches Minimum And 0.920 Inches Maximum
Actuation Type:	Push
Hardness Rating:	40.0 Rockwell C Minimum Shank
Hardness Rating:	40.0 Rockwell C Minimum Spindle
Shoulder To Head End Distance:	1.600 Inches Maximum
Pin Center To Handle End Distance:	1.730 Inches Minimum
Pin Attachment Type:	Link Or Ring
Detent To Tapered End Distance:	0.430 Inches Minimum And 0.460 Inches Maximum
Material:	Steel Comp 630 Shank Or Steel Comp 632 Shank
Material:	Steel Comp 630 Spindle Or Steel Comp 632 Spindle
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Shank Or Ams 5657 Assn Std 2nd Material Response Shank
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Spindle Or Ams 5657 Assn Std 2nd Material Response Spindle
Surface Treatment:	Passivate Shank
Surface Treatment:	Passivate Spindle
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Shank
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Spindle
Style Designator:	L Handle

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS17986C809> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.