

Description

Quick Release Pin part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS17986C839
Minimum Qty (MOQ):	1
NSN:	5315-01-368-5270
National Motor Freight:	105840, Nails / Spikes I / S Noi Plain Etc

NO IMAGE
AVAILABLE

P/N MS17986C839 Specifications

Shank Diameter:	0.4970 Inches Minimum And 0.4985 Inches Maximum
Detent Quantity:	2
Actuation Method:	Push Button
Grip Length:	3.900 Inches Minimum And 3.920 Inches Maximum
Actuation Type:	Push
Hardness Rating:	40.0 Rockwell C Minimum Shank40.0 Rockwell C Minimum Spindle
Shear Strength:	36800 Double Pound
Shoulder To Head End Distance:	1.600 Inches Maximum
Pin Center To Handle End Distance:	1.730 Inches Minimum And 1.850 Inches Maximum
Pin Attachment Type:	Link Or Ring
Detent To Tapered End Distance:	0.430 Inches Minimum And 0.460 Inches Maximum
Material:	Steel Comp 630 Shank Or Steel Comp 632 Shanksteel Comp 630 Spindle Or Steel Comp 632 Spindle
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Shank Or Ams 5657 Assn Std 2nd Material Response Shankams 5643 Assn Std 1st Material Response Spindle Or Ams 5657 Assn Std 2nd Material Response Spindle
Surface Treatment:	Passivate Shankpassivate Spindle
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Shankqq-p-35 Fed Spec Single Treatment Response Spindle
Style Designator:	L Handle

How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/MS17986C839> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.