

**Description**

Quick Release Pin part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |  |
|-------------------------|--|
| SKU / Model:            | MS17986C839                                |
| Minimum Qty (MOQ):      | 1  |
| NSN:                    | 5315-01-368-5270                           |
| National Motor Freight: | 105840, Nails / Spikes I / S Noi Plain Etc |

NO IMAGE  
AVAILABLE

## P/N MS17986C839 Specifications

|   |  |
|---|--|
| <b>Shank Diameter:</b>                                | 0.4970 Inches Minimum And 0.4985 Inches Maximum  |
| <b>Detent Quantity:</b>                               | 2  |
| <b>Actuation Method:</b>                              | Push Button  |
| <b>Grip Length:</b>                                   | 3.900 Inches Minimum And 3.920 Inches Maximum  |
| <b>Actuation Type:</b>                                | Push   |
| <b>Hardness Rating:</b>                               | 40.0 Rockwell C Minimum Shank40.0 Rockwell C Minimum Spindle   |
| <b>Shear Strength:</b>                                | 36800 Double Pound   |
| <b>Shoulder To Head End Distance:</b>                 | 1.600 Inches Maximum   |
| <b>Pin Center To Handle End Distance:</b>             | 1.730 Inches Minimum And 1.850 Inches Maximum  |
| <b>Pin Attachment Type:</b>                           | Link Or Ring   |
| <b>Detent To Tapered End Distance:</b>                | 0.430 Inches Minimum And 0.460 Inches Maximum  |
| <b>Material:</b>                                      | Steel Comp 630 Shank Or Steel Comp 632 Shanksteel Comp 630 Spindle Or Steel Comp 632 Spindle   |
| <b>Material Document And Classification:</b>          | Ams 5643 Assn Std 1st Material Response Shank Or Ams 5657 Assn Std 2nd Material Response Shankams 5643 Assn Std 1st Material Response Spindle Or Ams 5657 Assn Std 2nd Material Response Spindle |
| <b>Surface Treatment:</b>                             | Passivate Shankpassivate Spindle   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Shankqq-p-35 Fed Spec Single Treatment Response Spindle   |
| <b>Style Designator:</b>                              | L Handle   |

## How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/MS17986C839> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.