

Description

Quick Release Pin part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS17987C407
Minimum Qty (MOQ):	1
NSN:	5315-00-051-2358
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N MS17987C407 Specifications

Head Diameter:	0.310 Inches Minimum And 0.530 Inches Maximum
Shank Diameter:	0.2470 Inches Minimum And 0.2485 Inches Maximum
Ring Handle Diameter:	1.060 Inches Minimum
Detent Quantity:	2
Actuation Method:	Push Button
Grip Length:	0.700 Inches Minimum And 0.720 Inches Maximum
Actuation Type:	Push
Hardness Rating:	36.0 Rockwell C Minimum Shank And 40.0 Rockwell C Maximum Shank
Hardness Rating:	36.0 Rockwell C Minimum Spindle And 40.0 Rockwell C Maximum Spindle
Shoulder To Head End Distance:	0.780 Inches Minimum
Pin Attachment Type:	Hook Or Ring
Detent To Tapered End Distance:	0.260 Inches Minimum And 0.290 Inches Maximum
Material:	Steel Comp 4130 Shank
Material:	Steel Comp 4130 Spindle
Material Document And Classification:	Mil-t-6736 Mil Spec Single Material Response Shank Or Mil-s-6758 Mil Spec Single Material Response Shank
Material Document And Classification:	Mil-t-6736 Mil Spec Single Material Response Spindle Or Mil-s-6758 Mil Spec Single Material Response Spindle
Surface Treatment:	Cadmium Shank And Chromate Shank
Surface Treatment:	Cadmium Spindle And Chromate Spindle
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Shank
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Spindle
Style Designator:	Ring Handle

How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/MS17987C407> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.