

**Description**

MS17987C630 Quick Release Pin

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS17987C630
Minimum Qty (MOQ):	1
NSN:	5315-01-358-4828
ECCN:	EAR99
National Motor Freight:	105840, Nails / Spikes I / S Noi Plain Etc



## P/N MS17987C630 Specifications

<b>Head Diameter:</b>	0.450 Inches Minimum And 0.650 Inches Maximum
<b>Shank Diameter:</b>	0.3720 Inches Minimum And 0.3735 Inches Maximum
<b>Ring Handle Diameter:</b>	1.060 Inches Minimum
<b>Detent Quantity:</b>	2
<b>Actuation Method:</b>	Push Button
<b>Grip Length:</b>	3.000 Inches Minimum And 3.020 Inches Maximum
<b>Actuation Type:</b>	Push
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum Shank40.0 Rockwell C Minimum Spindle
<b>Shear Strength:</b>	20600 Double Pound
<b>Shoulder To Head End Distance:</b>	0.940 Inches Minimum
<b>Pin Attachment Type:</b>	Link Or Ring
<b>Detent To Tapered End Distance:</b>	0.335 Inches Minimum And 0.365 Inches Maximum
<b>Material:</b>	Steel Comp 630 Shank Or Steel Comp 632 Shanksteel Comp 630 Spindle Or Steel Comp 632 Spindle
<b>Material Document And Classification:</b>	Ams 5643 Assn Std 1st Material Response Shank Or Ams 5657 Assn Std 2nd Material Response Shankams 5643 Assn Std 1st Material Response Spindle Or Ams 5657 Assn Std 2nd Material Response Spindle
<b>Surface Treatment:</b>	Passivate Shankpassivate Spindle
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Shankqq-p-35 Fed Spec Single Treatment Response Spindle
<b>Style Designator:</b>	Ring Handle

## How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/MS17987C630> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.