

**Description**

MS17988C408 Quick Release Pin

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS17988C408
Minimum Qty (MOQ):	1
NSN:	5315-01-247-9490
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi

NO IMAGE  
AVAILABLE

## P/N MS17988C408 Specifications

<b>Head Diameter:</b>	0.360 Inches Minimum And 0.450 Inches Maximum
<b>Handle Length:</b>	1.375 Inches Minimum And 1.750 Inches Maximum
<b>Shank Diameter:</b>	0.2470 Inches Minimum And 0.2485 Inches Maximum
<b>Detent Quantity:</b>	2
<b>Actuation Method:</b>	Push Button
<b>Grip Length:</b>	0.800 Inches Minimum And 0.820 Inches Maximum
<b>Actuation Type:</b>	Push And Pull
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum Shank
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum Spindle
<b>Shoulder To Head End Distance:</b>	1.030 Inches Maximum
<b>Pin Attachment Type:</b>	Link Or Ring
<b>Detent To Tapered End Distance:</b>	0.410 Inches Maximum
<b>Material:</b>	Steel Comp 630 Shank Or Steel Comp 632 Shank
<b>Material:</b>	Steel Comp 630 Spindle Or Steel Comp 632 Spindle
<b>Material Document And Classification:</b>	Ams5643 Assn Std 1st Material Response Shank Or Ams5657 Assn Std 2nd Material Response Shank
<b>Material Document And Classification:</b>	Ams5643 Assn Std 1st Material Response Spindle Or Ams5657 Assn Std 2nd Material Response Spindle
<b>Surface Treatment:</b>	Passivate Shank
<b>Surface Treatment:</b>	Passivate Spindle
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec All Treatment Responses Spindle
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec All Treatment Responses Shank
<b>Style Designator:</b>	T Handle

## How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/MS17988C408> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.