

Description

MS17988C408 Quick Release Pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS17988C408
Minimum Qty (MOQ):	1
NSN:	5315-01-247-9490
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N MS17988C408 Specifications

Head Diameter:	0.360 Inches Minimum And 0.450 Inches Maximum
Handle Length:	1.375 Inches Minimum And 1.750 Inches Maximum
Shank Diameter:	0.2470 Inches Minimum And 0.2485 Inches Maximum
Detent Quantity:	2
Actuation Method:	Push Button
Grip Length:	0.800 Inches Minimum And 0.820 Inches Maximum
Actuation Type:	Push And Pull
Hardness Rating:	40.0 Rockwell C Minimum Shank
Hardness Rating:	40.0 Rockwell C Minimum Spindle
Shoulder To Head End Distance:	1.030 Inches Maximum
Pin Attachment Type:	Link Or Ring
Detent To Tapered End Distance:	0.410 Inches Maximum
Material:	Steel Comp 630 Shank Or Steel Comp 632 Shank
Material:	Steel Comp 630 Spindle Or Steel Comp 632 Spindle
Material Document And Classification:	Ams5643 Assn Std 1st Material Response Shank Or Ams5657 Assn Std 2nd Material Response Shank
Material Document And Classification:	Ams5643 Assn Std 1st Material Response Spindle Or Ams5657 Assn Std 2nd Material Response Spindle
Surface Treatment:	Passivate Shank
Surface Treatment:	Passivate Spindle
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec All Treatment Responses Spindle
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec All Treatment Responses Shank
Style Designator:	T Handle

How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/MS17988C408> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.