

Description

Quick Release Pin part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS17990C617
Minimum Qty (MOQ):	1
NSN:	5315-00-548-5226
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

P/N MS17990C617 Specifications

Head Diameter:	0.510 Inches Minimum And 0.630 Inches Maximum
Shank Diameter:	0.3720 Inches Minimum And 0.3735 Inches Maximum
Ring Handle Diameter:	1.000 Inches Minimum And 1.125 Inches Maximum
Detent Quantity:	2
Actuation Method:	Push Button
Grip Length:	1.700 Inches Minimum And 1.720 Inches Maximum
Actuation Type:	Pull And Push
Hardness Rating:	40.0 Rockwell C Minimum Shank
Hardness Rating:	40.0 Rockwell C Minimum Spindle
Shoulder To Head End Distance:	1.000 Inches Minimum
Pin Attachment Type:	Hook Or Ring
Detent To Tapered End Distance:	0.510 Inches Maximum
Material:	Steel Comp 630 Shank Or Steel Comp 632 Shank
Material:	Steel Comp 630 Spindle Or Steel Comp 632 Spindle
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Shank Or Ams 5657 Assn Std 2nd Material Response Shank
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Spindle Or Ams 5657 Assn Std 2nd Material Response Spindle
Surface Treatment:	Passivate Shank
Surface Treatment:	Passivate Spindle
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Shank
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Spindle
Style Designator:	Ring Handle

How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/MS17990C617> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.