

## P/N MS18063-14

## **Description**

Fastener Length: 1/4", Thread: 1/4-28, Head Width: 1/8", Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS1806314

Minimum Qty (MOQ): 10 EA

NSN: 5305-00-929-4617

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS18063-14 Specifications

_, , , ,	
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Maximum
Fastener Length:	0.250 Inches Nominal
Head Style:	Headless (setscrew)
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Point Style:	Cup
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.125 Inches Minimum And 0.127 Inches Maximum
Thread Quantity Per Inch:	28
Hardness Rating:	33.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

## **How to Order**

Order this setscrew from our inventory online by visiting <a href="https://military-fasteners.com/screws/setscrews/MS18063-14">https://military-fasteners.com/screws/setscrews/MS18063-14</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.