

**Description**

Fastener Length: 3/16", Thread: 4-40, Head Width: 3/64", Thread Length: 3/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS180635
Minimum Qty (MOQ):	10
NSN:	5305-00-931-3144
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE  
AVAILABLE

## P/N MS18063-5 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.188 Inches Maximum
<b>Fastener Length:</b>	0.188 Inches Nominal
<b>Head Style:</b>	Headless (setscrew)
<b>Locking Feature:</b>	Patch Grip Or Pellet Grip Or Strip Grip
<b>Point Style:</b>	Cup
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Width Across Flats:</b>	0.050 Inches Minimum And 0.051 Inches Maximum
<b>Thread Quantity Per Inch:</b>	40
<b>Hardness Rating:</b>	33.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type 2 Class 3 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/MS18063-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.