

P/N MS18063-9

Description

Fastener Length: 3/16", Thread: 1/4-28, Head Width: 1/8", Thread Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

National Motor Freight:

SKU / Model:	MS180639
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-916-4254
Schedule B:	7318.15.6080
ECCN:	EAR99

093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS18063-9 Specifications

_, , , ,	
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.188 Inches Maximum
Fastener Length:	0.188 Inches Nominal
Head Style:	Headless (setscrew)
Locking Feature:	Pellet Threads Or Strip Threads
Point Style:	Cup
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.125 Inches Minimum And 0.127 Inches Maximum
Thread Quantity Per Inch:	28
Hardness Rating:	33.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this setscrew from our inventory online by visiting https://military-fasteners.com/screws/setscrews/MS18063-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.