



Military-Fasteners.com

P/N MS18064-24

Description

Fastener Length: 3/8", Thread: 8-32, Head Width: 5/64", Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS1806424 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-056-3737 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS18064-24 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.375 Inches Minimum |
| Fastener Length: | 0.375 Inches Nominal |
| Head Style: | Headless (setscrew) |
| Locking Feature: | Strip Threads |
| Point Style: | Cup |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.164 Inches |
| Width Across Flats: | 0.078 Inches Minimum And 0.079 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 25.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Material: | Steel Corrosion Resisting Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS18064-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.