

**Description**

Fastener Length: 3/8", Thread: 8-32, Head Width: 5/64", Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS1806424
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-056-3737
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS18064-24 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.375 Inches Minimum
<b>Fastener Length:</b>	0.375 Inches Nominal
<b>Head Style:</b>	Headless (setscrew)
<b>Locking Feature:</b>	Strip Threads
<b>Point Style:</b>	Cup
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Width Across Flats:</b>	0.078 Inches Minimum And 0.079 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	25.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS18064-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.