

Description


Fastener Length: 1/4", Thread: 1/4-28, Head Width: 1/8", Thread Length: 1/4", MS18065 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1806514
Minimum Qty (MOQ):	10
NSN:	5305-01-038-4760
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS18065-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Headless (setscrew)
Locking Feature:	Strip Threads
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.125 Inches Nominal
Thread Quantity Per Inch:	28
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,c1 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 1 Style

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/MS18065-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.